


**Contact Caltel today**

01952 740 833

 E-mail – [sales@caltel.co.uk](mailto:sales@caltel.co.uk)
Visit us

Unit 4

Duncote mill

Walcott

Telford

TF6 5ER

**Technical**

- Standard voltage 240V – single phase
- All models can be supplied for 3 phase operation
- Suitable for hot (max 50°C) or cold\* water supply at 2 to 4 bar dynamic pressure
- Wash temperature – 60°C
- Rinse temperature – 80°C except 50 XL – 65°C


 80 XL, 91 XL,  
& 95 XL WSD


50 XL



51 XL

**Product Information**

- 1 year warranty
- Halcyon Amika models ruggedly built with simple controls
- 55 XL WSD with internal automatic water softener
- 95 XL WSD with internal automatic water softener
- Large three button controls on 50 XL
- Simple soft touch wipe clean controls on 51 XL, 55 XL WSD, 80 XL, 91 XL & 95 XL WSD
- All models fitted as standard with precise control peristaltic detergent and rinse aid dosing
- Drain pump as standard on 55 XL WSD & 95 XL WSD, optional on all other models
- Surface scrap trays standard on 91 XL & 95 XL WSD
- Surface scrap trays optional on 50 XL, 51 XL, 55 XL WSD & 80 XL
- 51 XL, 55 XL WSD, 91 XL & 95 XL WSD with internal break tank as standard

Drain pump versions require a waste up-stand for correct operation. Restrictive waste connections should be avoided for all installations.

\*Machines fitted to cold water supplies will not be capable of running repeated short cycles, the cycle time will automatically be extended to allow recovery of correct operating temperatures.

Dishwasher	Rack size mm	Useable Height	Dimensions W x D x H	Cycle time sec	Power KW	Amps required	Price
AM 50 XL	500	325	580 x 605 x 815	90/150	2.6/4.5/6.5	13/20/30###	£1425
AM 50 XLD	As AM 50XL above with fitted drain pump						£1526
AM 51 XL	500	325	580 x 605 x 815	90/150	2.6/4.5/6.5	13/20/30###	£1560
AM 51 XLD	As AM 51XL above with fitted drain pump						£1656
AM 55 XL WSD	500	325	580 x 605 x 815	90/150	2.6/4.5/6.5	13/20/30###	£1925
	AM 55XL WSD supplied with drain pump as standard						
AM 80 XL	500	380	640 x 740 x 1450	110/180	4.5/6.5	20/30###	£2378
AM 80 XLD	As AM 80 XL above with fitted drain pump						£2530
AM 91 XL	500	380	640 x 740 x 1450	110/180	4.5/6.5	20/30###	£2619
AM 91 XLD	As AM 91 XL above with fitted drain pump						£2778
AM 95 XL WSD	500	380	640 x 740 x 1450	90/120/180	4.5/6.5	20/30###	£2880
	AM 95 XL WSD supplied with fitted drain pump as standard						

# Height excludes feet which add 10 to 20mm.

## Height adjustable from 1455 to 1510mm – hood closed, 1885 to 1940mm – hood open.

### Machines will be supplied for 30-amp supply as standard, if 13 or 20 amp ordered they will be supplied with original cable and without plug. Standard 13-amp UK 3 pin plugs will be unsuitable for cable supplied. It is strongly recommended that for busy sites to achieve optimum performance that machines are installed on hot fill (max 50°C).

**ALL PRICES SUBJECT TO VAT**